

MAN

EPSILON S300L98 TGX 640 6X4

NY

TILGÆNGELIG




SPECIFIKATION

Crane: PK 24.001 SLD5

- Hydraulic 5-fold extension
- High-speed extension system with return oil recovery
- Swivel range 400°
- Hydraulic support leg extension (max.support width 6,600mm)
- Support leg extension 100mm
- support legs 180° tiltable
- Paltronic 40
- HPSC-E + LOAD
- Scanreco radio remote control (6L) linear levers
- Painting RAL3020
- Working lights on the articulated arm

TILBUDSINFORMATION

Lokationsdetaljer

France, 26250 - Frankrig 

Forhandler, detaljer

Palfinger France



Tilgængelighed

Tilgængelig

Produkttype

Ny

Forhandler, e-mail

loic.baritussio@palfinger.fr

Forhandler, telefon

0033628767400

- Hose equipment for two additional devices including quick coupling (multi-faster)

- 8.0to load hook

Superstructure: Tipper (KH Kipper)

- Inner dimensions 4,350 x 2,440 mm

- front wall height 1200 mm

- side wall height 800 mm

- Floor tipping bridge made of 5 mm Hardox

- Lashing rings in the floor panel and front wall

- Rear wall divided, upper part swingable and removable, lower part with 300 mm hydr. rock flap made of steel

Chassis: MAN

- TGS 28.510 6x4-4 BL CH

- 510 PS / 2.600 Nm

- Leaf suspension front axle, air suspension on both rear axles

- Fuel tank 300l / AD-Blue 35l

- Tires front 385/65/R22.5

- Tires rear 315/80/R22.5

- Cabin color: Traffic White RAL9016 / Chassis color: Graphite Black RAL9011

- trailer coupling RINGFEDER type RF50A

All pictures taken from a reference project

Producent	Palfinger	Rækkevidde / Løfteevne	9,80 m
Model	Epsilon S300L98	Mounting	front
Lastbilproducent	MAN	Hestekræfter	640 PS
Vehicle type	TGX 640 6x4	Emissionsnorm	Euro6
Førerhus	GM	Aksler	6x4
Akselafstand	3900 + 1400 mm	Nyttelast, kategori	6t - 15t

Grumier MAN



VINCENT

PALFINGER

PALFORET



MAN TGX 640 6X4

- Off-road category
- Front/Rear Axle Load (kg) : 10000 / 21000
- Rear pneumatic suspensions
- Cabin : GM
- Exhaust : In the track
- Wheelbase (mm) : 3900 + 1400
- Fuel Tank Capacity : 445L
- AdBlue Tank Capacity : 80L

TECHNICAL SPECIFICATIONS

EPSILON S300L98 Crane

- Reach at 9.80m, double telescopic
- Column-mounted seat with protective cover
- Comfort pack (heated seat, engine start/stop, acceleration +/-)
- Log combs
- Distributor protective cover
- 4 work lights 3000 lumen
- Rotating couplings at the base of the crane
- Grapple Hultdins SG520S



FLEXMAX Faymonville Trailer

- Rear trailer with 3-axle Flex-Z
- 1st axle mounted on a ball circle with hydromechanical steering
- 2nd and 3rd fixed axles
- BPW axles
- Centralized lubrication
- 30T turret on front and rear chassis



Metallization

- Extensions on front and rear chassis

ACCESSORIES

- Cabin guard with grapple support + 6 work lights
- Side protections in steel (tanks / battery compartment)
- 2 rear overhang compartments with chainsaw guide
- 2 telescopic supports for snow chains
- Aluminum hydraulic tank behind the cabin
- Double capacity cooler 30KW
- Storage compartment behind the cabin
- 6 work lights (side, rear, and on chassis)
- Shovel / broom support

