

MAN

P 300 KS

MAN TGL 8.190 4X2 BB

CONTRACT NUMBER: 15301364

NEW

SPECIAL OFFER

AVAILABLE NOW



SPECIFICATION

Performance data

- Working height approx. 30.00 m
- Cage floor height approx. 28.00 m
- Maximum outreach approx. 20.50 m
- Range of swivel table max. 540°
- Counter slewing system with two slewing rings rotating in opposite directions
- Slewing within the vehicle width
- Swivel range of cage boom 190°
- Rotation range of workman cage approx. +/- 85°
- Permissible inclination max. 5°
- Reduction in reach from 0.5°

Details


- High rigidity and stability thanks to multi-folded, high-strength fine-grained steel in each telescopic section
- Cage load sensor
- Device movements shut off when the basket touches the ground
- Covers made of aluminum chequer plate

Prior sale and changes reserved!

Print date: Jun 24, 2026, 8:34:07 AM

OFFER INFORMATION

Location details

Löbau, 02708 - Germany 

Dealer Name

Palfinger Platforms GmbH

Product type

New

Contract number

15301364

Dealer E-mail

sales.platforms@palfinger.com

Dealer phone

004935854796121

- Fully variable outrigger system with ground pressure monitoring
- Outrigger controls on the left and right of the base and in the workman cage
- Automatic deployment with vehicle tilt monitoring
- Can be operated without outriggers
- Engine start-stop function in the workman cage and at the base
- Modern, modular cage control panel with colour graphic display and robust cover
- Display showing possible directions of movement
- Display showing operating instructions
- Main movements continuously adjustable via two joysticks, up to 4 movements simultaneously
- Membrane keys easy to clean
- Home function in the workman cage and at the base
- Continuously variable proportional control
- Automatic cage arm assist function
- Sensitive cage levelling
- Hydraulic cage rotation mechanism with automatic centre position
- Voltage monitoring of the vehicle battery
- Earthing connections on the base frame and boom system
- Inspection log and operating instructions
- CE mark
- EC Declaration of Conformity

*The figures given above are standard values and may vary depending on the equipment and base vehicle

PRODUCT

Manufacturer	Palfinger	Turret rotation	540°
Model	P 300 KS	Basket size	1,60 m x 0,80 m x 1,10 m
Construction year	2025	Basket capacity	370 Kg
Outreach	20,50 m	Basket turning device	ca. +/- 85°
Max. height of work	30,00 m	Basket arm angle	195°
		Basket material	GRP-cage

TRUCK

Truck manufacturer	MAN	Wheel base	3.050 mm
Vehicle type	8,8 t	Power	140 kW (190 PS)
Construction year	2023	Emmission standard	EURO6
Drivers cabine	Compact CC cab	First registration	one day registration 12/2025
		TÜV / AU	No GSR II - Special Price